



For Product Enquiry Contact

Accusharp Cutting Tools Pvt. Ltd. W-242, J Block MIDC,Bhosari,Pune-411023 Tel:020-27129016, Fax:020-27124857 Email: accusharp@accusharp.co.in Website: www.accusharp.co.in

Metal Cutting Tools

Our Product Cluster:

Drills, Step drills, End-mills, Reamers, Cutters, Centre-drills, Form-Tools, Profile tools and Customised tooling solution in Solid Carbide and H.S.S.

For machining Components:

Engine Head, Cylinder Head, Connecting Rod, Wheels, Crank-Shafts, Gears, Crank-Case, Axles, Nozzle Ring, Wind-Mill Blade, etc.

In Work Material:

Carbon Steels, Alloy Steels, Cast Iron, Stainless Steel, Inconel, Super Alloys, Titanium Alloys, Copper Alloys, Aluminium Alloys, Brass, Plastics, etc.

For Industry Sectors:

- Automotive
- Energy
- Engineering
- Die & Mould
- Aerospace



For Product Enquiry Contact JIG Engineering

103/A, Mandpeshwar Ind Estate, Opp.M.C.F. Sports Cluib, Gymkhana Road, Borivali (W), Mumbai -400092, Maharashtra, India Tel: 7666335362 Website: www.edmwirecutfilter.com

Orbit Head Applications.

Converts the Z-axis vertical movement to an orbital movement.

- The ORBIT HEAD forms the whole depth of the thread in a single orbital cycle.
- No need for interfering with the machine's electronic circuits attach as an electrode holder and it's ready to operate.

Maintains the EDM machine features of sinking and withdrawal.

- Withdrawal of electrode designed so it is always towards the center of the hole and not in the direction from which it came in order to achieve improved flushing.
- Up to 3.2 mm (1/8") horizontal movement in 0.02 mm (0.001") increments.
- Special flexible hose for spraying fluid directly through the electrode for blind threads.
- Two positions for attachment of electrode.

Orbital fixed angular movement for threads (as well as circlip slot, inverted cone etc.)

• Orbital and rotating about its axis for circular symmetrical shapes.

A special electrode attachment enables the removal and replacement of the electrode without losing pre-settings for threads (to prevent cross-threading).